

CITY OF PINELLAS PARK
Building Development Division
Phone: 727-369-5647 Email: buildingdevelopment@pinellas-park.com



Permit # _____

Date _____

ROOF MITIGATION VERIFICATION STATEMENT
(Roof to Wall Connection)

Based upon my inspection, I have determined the installation was done according to the Hurricane Mitigation Retrofit Manual (based on 553.844 F.S.).

On _____ 20____, at _____ a.m./p.m., I personally inspected the roof to wall connection work at
(insert date)

(job site address)

CERTIFICATION

I certify that I am a (check one of the following):

- Licensed Roofing Contractor
- Licensed General, Residential, or Building Contractor
- Licensed FS468 Building Inspector
- Registered Architect or an Engineer in the State of Florida

Duly authorized by the State of Florida or its County's Municipalities to verify compliance with the Hurricane Provisions of HB 7057, Section 553.844 Florida Statutes. I also certify that I personally inspected the premises at the Location Address listed above on the date of this Statement. In my professional opinion, based on my knowledge, information and belief, I certify that the above statements are true and correct. Please complete the back side of this form and initial.

Date _____

License # _____

Signature _____

Phone # _____

*General, Building, Residential, or Roofing Contractor or any individual certified under 468 F.S. to make such an inspection.

Roof to Wall Connections for Hurricane Mitigation Retrofits

Job Address _____ Permit # _____

Roofing Contractor _____ License # _____

Value \$ _____ Method Used: RDC Value Insurance Policy

Required Uplift Capacities for Roof-to-Wall Connections for 145 mph Wind Loads (Pounds Per Linear Foot)

Framing Spacing ("o.c.) (circle one)		Roof Span (in feet) (circle one)							
		12'	20'	24'	28'	32'	36'	40'	Overhangs
Within 6 feet of building corner	12"	-186.0	-309.9	-371.9	-433.9	-495.9	-557.9	-619.9	-56.7
	16"	-247.4	-412.2	-494.7	-577.1	-659.6	-742.1	-824.5	-75.5
	24"	-372.0	-619.8	-743.8	-867.8	-991.8	-1115.8	-1239.8	-113.4
Greater than 6 feet from building corner	12"	-121.5	-202.5	-243.0	-283.5	-324.0	-364.4	-405.0	-56.7
	16"	-161.6	-269.4	-323.2	-377.1	-431.0	-484.7	-538.7	-75.5
	24"	-243.0	-405.0	-486.0	-567.0	-648.0	-728.8	-810.0	-113.4

Connector Information:

Connector #1 (within 6 feet of building corner):

Manufacturer _____ Model # _____ Uplift Rating _____

Connector #2 (greater than 6 feet from building corner):

Manufacturer _____ Model # _____ Uplift Rating _____

Initial